



# D40A to D65A Diode 24-250VDC Suppressor

LAD4D3U

M	ain	
•••	~	

Range	TeSys TeSys Deca
Device short name	LAD4
Product or component type	Suppressor module
Product compatibility	3P LC1D40AD80A 4P LC1DT60ADT80A

#### Complementary

Mounting location	Front
Mounting mode	By clips
Suppressor technology	Flywheel diode
[Uc] control circuit voltage	24250 V DC
Maximum peak voltage	1 Uc
Net weight	0.02 kg
Colour	Dark grey

#### **Environment**

Standards	IEC 60947-5-1 EN 60947-5-1 CSA C22.2 No 60947-5-1 UL 60947-5-1 GB/T 14048.5
Product certifications	UL CSA
IP degree of protection	IP2X conforming to IEC 60529
Ambient air temperature for operation	-2555 °C
Ambient air temperature for storage	-4080 °C

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2 cm
Package 1 Width	5 cm

Package 1 Length	3 cm
Package 1 Weight	19 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	6.2 cm
Package 2 Width	7.5 cm
Package 2 Length	12 cm
Package 2 Weight	191 g
Unit Type of Package 3	S01
Number of Units in Package 3	100
Package 3 Height	15 cm
Package 3 Width	15 cm
Package 3 Length	40 cm
Package 3 Weight	2.147 kg

## Offer Sustainability

0 1 : 11 % 11	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

#### **Contractual warranty**

Warranty 18 months

Recommended replacement(s)